

GLOBAL PUMP FUELCUBE



The transportable GLOBAL PUMP FUEL CUBE is a double-walled above ground fuel storage tank. It is specifically designed to provide on-demand fuel supply (environmentally and efficiently) for construction equipment and temporary power applications.

By transporting fuel to site with a GLOBAL PUMP FUELCUBE, you are ready to start up on arrival, without having to coordinate and wait for a fuel truck delivery. Once in place, the GLOBAL PUMP FUEL CUBE can be “quick-connected” directly to the engines of up to 3 pieces of diesel-powered equipment. Fuel can also be dispensed by manual or electric pump.

Extend your equipment run times, reduce your costs, and decrease the carbon footprint of your operations with the GLOBAL PUMP FUEL CUBE line of transportable fuel storage tanks!

FEATURES

Transportable.
Full load lifting eyes, forklift pockets and internal baffles designed to allow handling of the tank full of fuel.

Accessible.
Access manway for maintenance and inspection of inner tank. Removable inner tank for servicing and cleaning.

Environmentally Safe.
Double-walled, 110% containment eliminates the need for spill pans, UL 142 approved, designed to DOT standards.

Stackable.
Easily stackable (2)-high full of fuel and (3)-high empty to reduce storage space requirements.

Efficient.
ENVIROconnect Equipment Cabinet locks and secures equipment and fuel ports to run up to 3 pieces of diesel powered equipment.

MODELS AND SPECIFICATIONS	GP-10TCG	GP-20TCG	GP-30TCG	GP-40TCG
Length	46" (1,168 mm)	87" (2,210mm)	91" (2,311mm)	91" (2,311 mm)
Width	46" (1,168 mm)	46" (1,168 mm)	60" (1,524 mm)	87" (2,209 mm)
Height	52" (1,321 mm)	52" (1,321 mm)	52" (1,321 mm)	48" (1,219 mm)
Empty	1118 lbs (507 kg)	1825 lbs (828 kg)	2,153 lbs (977 kg)	27,24 lbs (1,236 kg)
Full	2994 lbs (1,358 kg)	5,574 lbs (2,528 kg)	7,765 lbs (3,522 kg)	9,370 lbs (4,250 kg)
Fuel Cell	264 Gal. (1,000 L)	528 Gal. (1,000 L)	792 Gal. (3,000 L)	1,000 Gal. (1,000 L)